GAM839

Heavy Duty All-Position Tire • Better Damage Resistance & Long Service Life



All position



Overview

Rim Sizes:20-22.5 Aspect Ratio:mm Section Width:210-305 Speed Rating:K-L

Features	Benefits
Reinforced belt construction	Protects casing from external punctures and delivers
	strong resistance against tread bursting
Strong casing with high tensile and thick cord structure	Strong casing strength for increase durability and
Strong dubling with high tensine and thick sord structure	
	reliability under continuous load stress
Giti Specially reinforced bead structure	Strong bead for better damage resistance in heavy load
	operating conditions
Special groove design in the center and V shape on the	Prevents and removes groove stone trapping,protecting
outer groove	the tire from road hazards
Unique shoulder groove design	Promotes heat dissipation and therefore cooler running,
	while preventing shoulder separation
Wear resistance and anti-cut and chip compound	Provides optimal wear life and resistant to damage from
wear resistance and anti-cut and only compound	
	cuts
Optimized rib ratio and high pattern block rigidity	Effectively improves pattern rigidity and uniform force
	distribution on the tread, reducing occurrence of irregular
	wear

Giti - GAM839 offers 4 different tyre sizes

	Tire Size	PR	Load Index	Speed	Approved	Outer	Tread	Max	kPa	PSI
				Rating	Rim	Diameter	Depth	Load(kg)		
						(mm)	(mm)			
TUBE TYPE	10.00R20	18PR	149/146	K	7.5	1054	16.2	3250/300 0	930/930	135/135
	11.00R20	18PR	152/149	К	8.0	1085	16	3550/325 0	930/930	135/135

TUBELESS	11R22.5	16PR	148/145	K	8.25	1054	16.2	3150/290 850/850 12	23/123
								0	
	12R22.5	18PR	152/149	L	9	1085	16	3550/325 930/930 13	35/135
								0	