

GAR558

Longer operating life • Irregular Wear Resistant •
Excellent Durability & Damage Resistant



All position



Overview

Rim Sizes:20-22.5
Aspect Ratio:mm
Section Width:210-279
Speed Rating:K-M

Features	Benefits
Widened tread width design	Large tread volume area for extended wear life
Four belt construction	Effectively optimizes crown stiffness and tire contact surface pressure, promoting long wear life
Special wear-resistant compound	Promotes long wear life
Optimal rib ratio and rigidity of tread pattern	Equalizes distribution of tire contact surface pressure, preventing tire from irregular wear
Advanced Equal Force Casing technology	Uniform force distribution enables optimal tire footprint at various loads level thus result in regular tread wear
Big groove wall design and Anti-stone trapping groove bottom	Effectively prevents stone trapping, protecting the tire from road hazards
Shoulder void design and zigzag longitudinal groove	Provides effective heat dissipation and better resistance against damages

Giti - GAR558 offers 7 different tyre sizes

	Tire Size	PR	Load Index	Speed Rating	Approved Rim	Outer Diameter (mm)	Tread Depth (mm)	Max Load(kg)	kPa	PSI
TUBE TYPE	8.25R20	16PR	139/137	K	6.5	974	14	2430/2300	930/930	135/135
	9.00R20	16PR	144/142	K	7	1019	14.5	2800/265	900/900	130/130

TUBELESS								0		
	10.00R20	18PR	149/146	K	7.5	1054	15	3250/300	930/930	135/135
								0		
	11.00R20	18PR	152/149	K	8	1085	15.3	3550/325	930/930	135/135
								0		
	9R22.5	14PR	136/134	M	6.75	974	14	2240/212	830/830	120/120
								0		
	10R22.5	16PR	144/142	M	7.50	1019	14.8	2800/265	900/900	130/130
							0			
	11R22.5	16PR	148/145	M	8.25	1054	15.8	3150/290	850/850	123/123
							0			