GDR655

Superior Traction • Longer Mileage



Drive



Overview

Rim Sizes:22.5
Aspect Ratio:0-80mm
Section Width:279-315
Speed Rating:L-M

Features	Benefits					
Specially arranged block and sipe angle	Enhanced traction driving performance					
Four belt construction	Increases casing and tread stiffness, minimizing tire					
	deformation for longer wear					
Advanced Equal Force Casing technology	Uniform force distribution enables optimal tire footprint at various loads level thus result in regular tread wear					
Widened tread width design	Large tread volume area for extended wear life					
Extended tread depth	Higher tread volume for longer mileage driving capabilities					
Giti specially-formulated tread compound	Improved wear resistance of tread					
Unique inter-dependant blocks at tread pattern center	Limits block movement, effectively reducing abnormal wear					
FEA bead construction with bead optimization	Optimizes and uniformly distributes load pressure to the bead, minimizing damage					

Giti - GDR655 offers 4 different tyre sizes

	Tire Size	PR	Load Index	Speed	Approved	Outer	Tread	Max	kPa	PSI
				Rating	Rim	Diameter	Depth	Load(kg)		
						(mm)	(mm)			
TUBELESS	295/80R22.5	18PR	152/149	М	9.00	1044	21.1	3550/325 0	900/900	130/130
	315/80R22.5	18PR	156/150(154/150)	L(M)	9.00	1076	21	4000/335 0	850/850	123/123
	315/70R22.5	20PR	154/150(152/148)	L(M)	9.00	1014	21	3750/335	900/900	131/131

11R22.5 16PR 148/145 M 8.25 1050 21 3150/290 850/850 123/123 0