

GDR665

Specially arranged block and sipe angle



Drive



Overview

Rim Sizes:22.5
Aspect Ratio:80mm
Section Width:275-315
Speed Rating:L-M

Features	Benefits
Specially arranged block and sipe angle	Enhanced traction driving performance
Four belt construction	Increases casing and tread stiffness, minimizing tire deformation for longer wear
Advanced Equal Force Casing technology	Uniform force distribution enables optimal tire footprint at various loads level thus result in regular tread wear.
Widened tread width design	Large tread volume area for extended wear life
Extended tread depth	Higher tread volume for longer mileage driving capabilities
Giti specially formulated tread compound	Improved wear resistance of tread
Directional deep tread pattern design	Delivers excellent traction, provides optimal mileage performance and reduces irregular wear

Giti - GDR665 offers 3 different tyre sizes

	Tire Size	PR	Load Index	Speed Rating	Approved Rim	Outer Diameter (mm)	Tread Depth (mm)	Max Load(kg)	kPa	PSI
TUBELESS	295/80R22.5	18PR	152/149	M	9.00	1044	21.1	3550/3250	900/900	130/130
	315/80R22.5	18PR	156/150(154/150)	L(M)	9.00	1076	21	4000/3350	850/850	123/123
	315/80R22.5	18PR	156/150(154/150)	L(M)	9.00	1076	21	4000/3350	850/850	123/123