GSR225

Resist Irregular Wear • Longer Mileage • Better in Handling



Steer



Overview

Rim Sizes:19.5-22.5	Features	Benefits			
Aspect Ratio:0-80mm Section Width:225-315 Speed Rating:J-M	Four belt construction	Increases casing and tread stiffness, minimizing tire deformation for longer wear			
	Advanced Equal Force Casing technology	Uniform force distribution enables optimal tire footprint at various loads level thus result in regular tread wear			
	Widened tread layout	Large tread volume for extended wear life			
	Giti specially-formulated tread compound	Improved wear resistance of tread			
	Resilient four vertical groove and zig-zag bottom design	Provides better handling and controllability of vehicle			
	Mutiple sipes along the side of groove	Self cleaning capability and higher resistance to damage from road hazards			
	Tire casing designed for retreadability	Higher retreadable capabilities			
	FEA bead construction optimization concept for bead construction	Optimizes and uniformly distributes load pressure to the bead, minimizing damage			

Giti - GSR225 offers 4 different tyre sizes

	Tire Size	PR	Load Index	Speed	Approved	Outer	Tread	Max	kPa	PSI
				Rating	Rim	Diameter	Depth	Load(kg)		
				1		(mm)	(mm)			
TUBELESS	225/70R19.5	14PR	128/126	L	6.75	811	13	1800/170	760/760	110/110
								0		
	245/70R19.5	18PR	141/140	М	7.50	839	14	2575/250	860/860	125/125
								0		
	245/70R19.5	16PR	136/134	М	7.50	839	14	2240/212	830/830	120/120
								0		

285/70R19.5 16PR	146/145	М	8.25	895	14.5	3000/290	900/900	130/130
						0		